



Havoline® Ultra R SAE 5W-30

Premium performance synthetic low SAPS engine lubricant

Product description

Havoline Ultra R SAE 5W-30 is a premium performance synthetic multigrade engine lubricant. Havoline Ultra R SAE 5W-30 is a low SAPS lubricant, formulated with synthetic base stocks and advanced technology additives offering low levels of sulphated ash, phosphorus and sulphur.

Havoline Ultra R SAE 5W-30 is suitable for use in naturally aspirated and turbocharged gasoline and diesel passenger cars, and light duty commercial diesel engines. Havoline Ultra R SAE 5W-30 has been designed to perform under severe operating conditions as defined by the engine manufacturer.

Customer benefits

- Suitable for cars equipped with modern catalysts (TWCs) or diesel particulate filters (DPFs)
- Low levels of ash-forming phosphorus and sulphur additive (low SAPS) formulation helps extend DPF and TWC service life
- Aids reliable, wide temperature engine performance and protection
- Advanced performance detergency and dispersancy system assists in keeping engines clean
- Formulated to contribute to high-level engine wear and corrosion protection

Applications

- Havoline Ultra R SAE 5W-30 is recommended for use in high performance naturally aspirated and turbocharged car and light van diesel and gasoline engines equipped with modern three way catalysts (TWC) and diesel particulate filters (DPF) requiring low SAPS oils. This engine oil will help increase the lifetime of the TWC and the DPF

Product highlights

- **Synthetic low SAPS lubrication technology**
- **Suitable for cars fitted with TWCs and DPFs**
- **Helps extend TWC and DPF service life**
- **Reliable wide temperature performance**
- **Aids keep-clean engine performance**
- **Contributes to wear and corrosion protection**

Selected specification standards include:

ACEA

Mercedes Benz

Renault

Approvals, performance and recommendations

Approvals

- Renault RN 0720
- MB approval 226.51

Performance

Havoline Ultra R 5W-30 meets:

- ACEA C4

Typical test data		
Test	Test methods	Results
Viscosity Grade		SAE 5W-30
Shelf Life: 60 months from date of filling indicated on the product label		
Density, 15°C, kg/l	ASTM D4052	0.853
Visc, Kinematic, 40°C, mm ² /s	ASTM D445	67.1
Visc, Kinematic, 100°C, mm ² /s	ASTM D445	11.5
Viscosity Index	ASTM D2270	167
Pour Point, °C	ASTM D97	-39
Flash Point COC, °C	ASTM D92	233

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

Disclaimer Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheets.

Health, safety, storage and environmental Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDSs are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

A Chevron company product